

Entry Level Laminators



Economic and budget friendly platform designed for easy entry into the sign and print market.



Highlights

- **Variable Speed Control** – Fast lamination speeds of over 16 feet per minute (RSC-1401CLTW)
- **Quick Notch Gap Adjustment** – Eliminating guess work when setting the nip for mounting
- **Crowned Silicon Rollers** – Ensures proper tracking and lasts longer than rubber rollers
- **Operator Friendly** – Easy to use digital controls and convenient foot pedal for hands free operation

Entry Level Laminators



**FAST
SPEEDS**

**UP TO 5/8"
MOUNTING**

**CONVENIENT
FEATURES**



HIGHLIGHTS

Maximum Width	
RSC-1401CLTW	55" (1400 m)
RSC-820CLS	32" (820 mm)
Maximum Speed	
RSC-1401CLTW	16 ft./min. (5 m./min.)
RSC-820CLS	8.2 ft./min. (2.5 m./min.)
Mounting	
RSC-1401CLTW	Up to 5/8"
RSC-820CLS	Up to 9/32"
Rear Cross Cutter	RSC-820CLS
Foot Pedal	Yes
Reverse	Yes
Safety	
RSC-1401CLTW	Photoelectric Sensors
RSC-820CLS	Safety Shield
Shaft Size	3" Auto-Grips

DIMENSIONS & WEIGHT

Dimensions (WxDxH)	
RSC-1401CLTW	67" x 22" x 43"
RSC-820CLS	41" x 21" x 43"
Weight	
RSC-1401CLTW	286 lbs.
RSC-820CLS	188 lbs.
Crate Dimensions (WxDxH)	
RSC-1401CLTW	79" x 31" x 28"
RSC-820CLS	51" x 31" x 24"
Crate Weight	
RSC-1401CLTW	396 lbs.
RSC-820CLS	221 lbs.
UPC Code	
RSC-1401CLTW	8 49023 07038 2
RSC-820CLS	8 49023 07010 8

**Warranty
Parts & Labor 1 Year**